


10PPHQ+CE...-2B/2K SERIES ELECTRIC PPH VALVE



Parameter & Dimensions (mm)

Product Parameter				
Caliber		DN15-DN100 (1/2"-4")		
Voltage		AC220V	DC24V	AC110V
Power		100W	100W	100W
Rated Current		0.6A	1.5A	1.0A
Running Time		26s	8s	26s
Control Type		Two-wire fail-safe open close type		
Pressure		PN10		
O-ring		EPDM (Customized FKM)		
Material	Valve Body	PPH		
	Ball Plate	PPH		
	Seat Sealing	PTFE		
Temperatue		0~80℃ 32~176°F		
Connection Type		True Union Heat Fusion /Threaded		
Applicable Medium		Water, air, oil,weak acid-base solution corrosive medium...		

YIMIER Electric Ball Valve

Model	Caliber	d	W	W1	H1	L	H	Weight (kg)
10PPHQ+ CEA220-2B/2K 10PPHQ+ CEA110-2B/2K 10PPHQ+ CED24-2B/2K	DN15	19	145	250	160	108	63	3.48
	DN20	24	145	250	160	118	75	3.55
	DN25	31	145	250	160	132	82	3.65
	DN32	39	145	250	160	148	95	3.82
	DN40	49	145	250	160	160	111.5	4.02
	DN50	62	145	250	160	182	135	4.46
	DN65	74	145	250	160	205	173	4.91
	DN80	88	145	250	160	227	205	5.92
	DN100	110	145	250	160	259	238	7.87

Wiring Diagram

