

PH(S) Series Pneumatic Valves

Produit Overview




A pneumatic actuator is an actuating device that uses air pressure to drive the opening, closing, or adjustment of valves. It is also called a pneumatic actuator mechanism or pneumatic device. Pneumatic actuators are sometimes equipped with certain auxiliary devices. Commonly used ones include valve positioners and handwheel mechanisms. The function of a valve positioner is to use feedback principles to improve the performance of the actuator, enabling it to achieve precise positioning according to the controller's control signal. The function of a handwheel mechanism is to allow direct manual operation of the control valve to maintain normal production when the control system fails due to power outages, loss of air supply, controller output failure, or actuator malfunction.

Produit parameter

Cylinder Parameter			
Model	PH Series Actuator	Control type	Single acting/double acting
Max. rotation angle	90°~92°	Forms Type	cut
Control air source	Dry, clean air	Air Source Pressure	0-4~0.7MPa
Operating temperature	-20℃~50℃ / -4°F ~ 122°F	Shaft	Steel
Cylinder	Aluminum alloy	O-ring	NBR
Pistons	Die-cast aluminum	End closure	Die Casting Aluminum Alloy

Dimensions (mm)




YIMIER Pneumatic Valves

Produit Model	L	W	H
PH32	111	47	72
PH52	146	80	100
PH63	164	84	116
PH75	184	98	128

Name	Function	Picture
Limit Switch (Standard Type)	A signal device for the remote control of pneumatic valves. It indicates the operating status of the valve by the opening and closing actions of the valve.	
Plate type solenoid valve	Solenoid valves enable remote control of the opening and closing of pneumatic valves. Two voltage options are available: DC24V and AC220V.	
Filter Regulator Unit	It is installed at the front end of the air source inlet to stabilize the air source pressure and filter impurities in the air source, so as to ensure the safe operation of the pneumatic valve.	

10UPYQ+PH(S)... Series Pneumatic UPVC Ball Valves



Parameter & Dimensions (mm)

Valve parameter	
Caliber	DN15-DN100
Pressure	PN10
O-ring material	EPDM
Material	Body
	Plate
	Seat sealing
Temperature	0 ~ 60°C / 32 ~ 140°F
Connection method	Double union
Applicable Medium	Water, air, oil, corrosive medium

Model	Caliber	d	L1	W	H1	L	H2
10UPYQ+PH(S)	DN15	21.3	111(146)	47(80)	72(100)	120	64
	DN20	26.7	146	80	100	135	76
	DN25	33.4	146	80	100	150	82.5
	DN32	42.2	146	80	100	167	96
	DN40	48.3	146	80	100	178	112.5
	DN50	60.3	146	80	100	204	136
	DN65	73	164(184)	84(98)	116(128)	234	163.5
	DN80	88.9	164(184)	84(98)	116(128)	259	191.5
	DN100	114.3	184	98	128	311	232