

CE SERIES ELECTRIC VALVE

Product overview

1. The actuator is equipped with manual adjustment function, the valve and actuator connection adopts tight top screws, stem cardboard connection, convenient and fast easy to connect, easy to site installation and commissioning.
2. The power supply of electric actuator usually has: AC220V, AC380V, AC24V and so on. After the electric actuator and valve stem are connected and debugged; Another regulating type (0-10V or 4-20mA signal) optional optional.



Product Model

CEA220S Passive contact type(S) AC220V
CEA220-SA CEA/D24-SA Intelligent control type (Z) Input signal 4....20mA
CEA220-SV CEA/D24-SV Intelligent control type (Z) Input signal 0....10V

Product parameter


30Nm Actuator Parameter			
Voltage	AC220V	Connection	Passive contact type / Intelligent regulation type / DC motor
Power	8W	Rotation angle	0°-90°
Rated current	0.036A	Protection level	IP67
Output torque	30Nm	Mounting direction	Mounting at any angle
Running time	20s	Temperature	-30℃~60℃

50Nm Actuator Parameter				
Voltage	DC24V	AC24V	AC110V	AC220V
Power	13W	15W	15W	15W
Rated current	1.28A	1.50A	0.24A	0.15A
Running time	8s	26s	26s	26s
Output torque	50Nm			
Connection	Passive contact type/Intelligent regulation type/DC motor type			
Rotation angle	0°-90°			
Protection level	IP67			
Mounting direction	Installation at any angle			
Temperature	-30℃~60℃			

100/160/200Nm Actuator Parameter				
Voltage	DC24V	AC24V	AC110V	AC220V
Power	25W	30W	30W	30W
Rated current	2.03A	2.12A	0.57A	0.30A
Running time	10s/20s	30s/60s	30s/60s	30s/60s
Output torque	100Nm	160Nm/200Nm	160Nm/200Nm	160Nm/200Nm
Connection	Passive contact type/Intelligent regulation type/DC motor type			
Rotation angle	0°-90°			
Protection level	IP67			
Mounting direction	Installation at any angle			
Temperature	-30℃~60℃			


© 2010 Pearson Education, Inc. or its affiliate(s). All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without permission in writing from Pearson Education, Inc.

Wiring Diagram




Contact type without edge > 50Nm

Voltage: AC220V Suitable for Model CEA220S
(Switching type Passive contact feedback)




Contact type without edge < 50Nm

Voltage: AC220V Suitable for Model CEA220S
(Switching type Passive contact feedback)



Intelligent adjustment type

Voltage: AC220V, AC24V, DC24V
Applicable models: CEA220-SA/SV, CEA24-SV/SA,
CED24-SA/SV Actuator
(Regulating type Signal: 0-10V/4-20mA)




DC motor type

Voltage: DC24V Suitable for model CED24S actuator


YIMIER Electric Valve

Dimensions (mm)


30Nm



50Nm



100/160/200Nm



10PEPD+CE... Series Electric PPH Butterfly Valve





Product Overview

Electric PPH Butterfly Valve, a corrosion-resistant electric plastic butterfly valve. The valve body features acid-alkali corrosion resistance and supports convenient flanged / wafer installation. Equipped with an electric actuator. Optional types: passive contact type / intelligent modulating type / DC motor type. Widely used for automatic control of anti-corrosion pipelines in water treatment, chemical, environmental protection and irrigation.

Parameter & Dimensions (mm)

Valve parameter			
Caliber		DN50-DN200	
Pressure		PN10	
Material	Body	PPH	
	Plate	PPH	
	Seat sealing	EPDM	
Temperature		0~80℃	
Connection		Double—clip	
Applicable Medium		Water, air, oil, corrosive medium	



Model	Caliber	W	L	H1	C	D	H2
(AC220V) 10PEPD+CEA220S Switching	DN50	135	140	126	123	54	194.5
	DN65	135	140	126	143	67	221
	DN80	135	140	126	157	83	239.5
	DN100	145	168	160	186	101	278
	DN125	155	203	165	213	127	284
	DN150	155	203	165	240	152	315
	DN200	155	203	165	296	200	385

Model	Caliber	W	L	H1	C	D	H2
(DC24V) 10PEPD+CED24S Switching	DN50	145	168	160	123	54	194.5
	DN65	145	168	160	143	67	221
	DN80	145	168	160	157	83	239.5
	DN100	145	168	160	186	101	278
	DN125	155	203	165	213	127	284
	DN150	155	203	165	240	152	315
	DN200	155	203	165	296	200	385

Model	Caliber	W	L	H1	C	D	H2
(AC220V) 10PEPD+CEA220SA/SV Modulating (DC24V) 10PEPD+CED24SA/SV Modulating	DN50	145	168	160	123	54	194.5
	DN65	145	168	160	143	67	221
	DN80	145	168	160	157	83	239.5
	DN100	145	168	160	186	101	278
	DN125	155	203	165	213	127	284
	DN150	155	203	165	240	152	315
	DN200	155	203	165	296	200	385